

RUN LIME

TDS65 Rev3 01/08/18

DESCRIPTION

Calcium Hydroxide – Run Lime (Fine grade for cornice work and lime washes).

USES

Limes are the base of most traditional mortars and plaster mixes. Limes should be slaked for a minimum of 14 days prior to use when using in finishing materials. Slaked Limes are also used in our pre-mixed mortars.

TECHNICAL DATA

Run Lime SG 1-1 to 1-3

PREPARATION

To remove excess water from any of the slaked Limes, pour the lime into a ring made in a sand pit and leave overnight.

MIXING

Lime mortars can be mixed by hand or by mechanical mixers

APPLICATION

For specific uses and formulations containing Lime products consult our technical department.

PRECAUTIONS

All Limes are caustic and care should be taken and the correct safety equipment worn when handling these materials

PACKAGING

20 Litre.

200 Litre.

STORAGE

Storage life is indefinite provided the Lime is not allowed to dry out.

SHELF LIFE

3 years.

SAFETY

Refer to Westgate Pty Ltd Safety Data Sheet (SDS) for instructions.



Westgate Pty Ltd
16 Frost Road, Campbelltown NSW 2560
Ph: 61 2 46285010 Fax: 61 2 46285020
Email: info@westox.com Website: www.westox.com